

IN THE CLAIMS

Original

7/9/03

- Sub
DX
C
1. (Previously Amended) In a client device, a method comprising:
dynamically obtaining by the client device at least one alert detection parameter from a first server;
dynamically obtaining configuration data from a remote alert proxy using the at least one obtained alert detection parameter; and
automatically configuring the client device using the dynamically obtained configuration data.
2. (Original) The method of claim 1, wherein the automatically configuring the client device using the dynamically obtained configuration data further comprises enabling the client device to detect alerts.
- Sub
DX
3. (Original) The method of claim 2, wherein the client device is enabled to detect alerts while in a reduced functional state.
4. (Original) The method of claim 3, wherein the reduced functional state includes an operating system unavailable state.
5. (Original) The method of claim 1, wherein the first server operates according to a dynamic host control protocol (DHCP).

6. (Previously Amended) The method of claim 1, wherein the at least one alert detection parameter is requested by the client device from the first server.
7. (Previously Amended) The method of claim 6, wherein the at least one alert detection parameter is requested by the client device using the options field of a dynamic host control protocol (DHCP) message.
8. (Previously Amended) The method of claim 1, wherein dynamically obtaining by the client device the at least one alert detection parameter further comprises dynamically obtaining at least one of an alert destination address, a watchdog interval, and a heartbeat interval.
9. (Original) The method of claim 8, wherein the alert destination address uniquely identifies the remote alert proxy on a network.
10. (Original) The method of claim 1, wherein the configuration data is dynamically obtained from a remote alert proxy through a remote management and control protocol (RMCP).
11. (Previously Amended) In a first server, a method comprising:
- receiving by an alert proxy, a configuration data request from a client device, the configuration data request being submitted by the client device using at least one dynamically obtained alert detection parameter, and
- providing the requested configuration data to the client device to enable the client device to be automatically configured.

12. (Previously Amended) The method of claim 11, wherein the at least one dynamically obtained alert detection parameter is dynamically obtained from a second server.
13. (Original) The method of claim 12, wherein the second server operates according to a dynamic host control protocol (DHCP).
14. (Previously Amended) The method of claim 12, wherein the at least one dynamically obtained alert detection parameter includes at least one of a dynamically obtained alert destination address, a watchdog interval, and a heartbeat interval.
15. (Original) The method of claim 14, wherein the dynamically obtained alert destination address uniquely identifies the first server on a network.
16. (Original) The method of claim 11, wherein the requested configuration data is provided to the client device through a remote management and control protocol (RMCP).
17. (Original) The method of claim 11, wherein the providing the requested configuration data to the client device to enable the client device to be automatically configured further comprises enabling the client device to detect alerts.
18. (Original) The method of claim 17, wherein the client device is enabled to detect alerts independent from whether an operating system is operable on the client device.

Application No.: 09/409,627
Attorney Docket No.: 042390.P7092

Examiner: K. Parton
Art Unit: 2153

19. (Previously Amended) An apparatus comprising logic to:
- dynamically obtain at least one alert detection parameter from a first server;
 - dynamically obtain configuration data from a remote alert proxy using the at least one obtained alert detection parameter; and
 - configure the apparatus using the dynamically obtained configuration data.
20. (Previously Amended) The apparatus of claim 19, wherein the at least one obtained alert detection parameter includes at least one of an alert destination address, a watchdog interval, and a heartbeat interval.
21. (Original) The apparatus of claim 19, wherein the logic configures the apparatus to:
- detect alerts while the apparatus is in an operating system unavailable state.
22. (Previously Amended) An article of manufacture comprising a machine readable medium having a plurality of machine readable instructions stored thereon, wherein when the instructions are executed by a processor, the instructions subscribe the processor to:
- dynamically obtain at least one alert detection parameter from a first server;
 - dynamically obtain configuration data from a remote alert proxy using the at least one obtained alert detection parameter; and
 - configure a device containing the processor using the dynamically obtained configuration data.

D3
OK
Cant

23. (Original) The article of manufacture of claim 22, wherein the instructions further subscribe the processor to configure the device to:

detect alerts while the device is in a reduced functional state.

24. (Previously Amended) The article of manufacture of claim 22, wherein the at least one obtained alert detection parameter includes at least one of an alert destination address, a watchdog interval, and a heartbeat interval.

✓

25-31. (Cancelled)